

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
15 March 2001 (15.03.2001)

PCT

(10) International Publication Number
WO 01/17713 A1

(51) International Patent Classification⁷: **B22D 11/15**

(21) International Application Number: PCT/SE00/01598

(22) International Filing Date: 22 August 2000 (22.08.2000)

(25) Filing Language: Swedish

(26) Publication Language: English

(30) Priority Data:
9903146-0 ✓ 3 September 1999 (03.09.1999) SE

(71) Applicant (for all designated States except US): **ABB AB**
[SE/SE]; S-721 83 Västerås (SE).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **SVAHN, Conny**
[SE/SE]; Rekylgatan 10, S-723 38 Västerås (SE).
KROON, Tord [SE/SE]; Dybecksgatan 22E, S-722 22
Västerås (SE).

(74) Agents: **OLSSON, Jan et al.**; Bjerkéns Patentbyrå KB,
Box 1274, S-801 37 Gävle (SE).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, CZ (utility model), DE, DE (utility model), DK, DK (utility model), DM, DZ, EE, ES, FI, FI (utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (utility model), SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:

With international search report.

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: A DEVICE FOR CONTINUOUS OR SEMI-CONTINUOUS CASTING OF METALS



(57) Abstract: A device for continuous or semi-continuous casting of metals comprises an electromagnetic brake comprising at least two magnetic cores (25, 26; 27, 28), arranged on one side of a mould (31) and attached thereto, and a yoke (32, 33) which is detachably connected to the two magnetic cores (25, 26; 27, 28) and interconnects them. The yoke (32, 33) carries at least one coil (36, 37). The coil (36, 37) is wound around the yoke (32, 33) substantially between the two magnetic cores (25, 26; 27, 28) interconnected by the yoke (32, 33). The yoke (32, 33) has two separate surfaces (46, 47; 48, 49) being adapted to detachably abut against one magnetic core (25, 26; 27, 28) each, and the coil (36, 37) is wound around the yoke (32, 33) substantially between said surfaces (46, 47; 48, 49).

WO 01/17713 A1